NATIONAL AIR INTELLIGENCE CENTER



LUMINESCENCE PROPERTIES OF ZnWO4:Cr3+ LASER CRYSTALS

by

Zang Jingcun, Wu Shaohua, Ma Yue





DTIC QUALITY INCPECTED 6

Approved for public release; Distribution unlimited.

19950407 091

HUMAN TRANSLATION

NAIC-ID(RS)T-0496-94

30 March 1995

MICROFICHE NR:95000131

LUMINESCENCE PROPERTIES OF ZnWO4:Cr3+ LASER CRYSTALS

By: Zang Jingcun, Wu Shaohua, Ma Yue

English pages: 7

Source: Zhongguo Jiguang, Vol. 18, Nr. 6, June 1991;

pp. 446-449

Country of origin: China

Translated by: Leo Kanner Associates

F33657-88-D-2188

Requester: NAIC/TATD/Larry Ward

Approved for public release; Distribution unlimited.

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE NATIONAL AIR INTELLIGENCE CENTER.

PREPARED BY:

TRANSLATION SERVICES
NATIONAL AIR INTELLIGENCE CENTER
WPAFB, OHIO

NAIC-ID(RS)T-0496-94

Date

30 March 1995

GRAPHICS DISCLAIMER

All figures, graphics, tables, equations, etc. merged into this translation were extracted from the best quality copy available.

Acces	sion For	·M.S:-
NTIS	GRAMI	I I
DTIC	TAB	ā.
Unann	ounced	
Justi	fication	
Ву		
Pistr	ibution/	V.
Avai	lability	Codes
	Avail and	1/or
Plat	Special	
A:1		

LUMINESCENCE PROPERTIES OF ZnWO4:Cr3+ LASER CRYSTALS

Zang Jingcun, Wu Shaohua, and Ma Yue, of Beijing Polytechnic University, Beijing 100022

Abstract: Luminescence properties of Zn WO₄:Cr³⁺ laser crystals were investigated. ⁴T₂ energy level of Cr³⁺ splitted to three levels, 13550, 14205 and 14706 cm⁻¹, and the Stokes-shift of luminescence spectra is 236 nm. The best intensity peak of emission is at 912 nm. If the excitation wavelength was selected as 608 nm and doping concentration was 0.01 wt%, a broad emission band would be observed at 532 nm excitation.

Key words: ZnWO4:Cr3+ crystals, luminescence, spectra

In recent years, solid tunable laser crystals have seen considerable development. Since Cr3+ ions are stable in electrovalence and exhibit wide absorption bands, there is wideband fluorescence emission with "T2 - A. , therefore there have been considerable widespread research on various materials of Cr^{3†} as the excitation agent [1,3]. ZnWO₄: Or^{3†} laser crystals can execute continuous and tunable laser oscillation within the frequencies 900 to 1080nm, so these crystals are emphasized by researchers [4]. However, since the ZnWO4 structure has low symmetry, and since there is still inconsistent views in the analysis of optical spectra, and high-grade complete monocrystals are not readily available, there has not been extensive studies This paper reports on research on their luminescence properties. results on the luminescence properties of high-grade monocrystals with dislocation density lower than $5 \times 10^2 \text{cm}^2$. These monocrystals were grown by the authors.

I. Experimental Results and Discussion

1.1. Absorption spectra

The zinc tungstate monocrystals are of the P2/C space group. After doping with x-ray analysis, there is no change in its fundamental structure. With different amounts of the dopant Cr³⁺, the cell parameters change slightly. concentration of Cr_2O_3 is 0.05% by weight (indicating the constituent concentration, as below), the crystal cell volume'is at a minimum. The crystal cell parameters are a=0.46835nm, b=0.56910nm, c=0.49211nm, β =90.53°. These quantities are used as the basis for x-ray orientation. The direction of light passage is the polarization absorption light spectrum for [100] and [010], as shown in Fig. 1. The test instrument is the UV-265 ultraviolet visible light spectrophotometer. From the figure, we can see that there are two main absorption bands for $ZnWO_{\delta}:Cr^{3\dagger}$. The main absorption bands correspond, respectively, to ${}^{4}T_{1}$ and ${}^{4}T_{2}$ energy levels, based on splitting of $d^3(^4F)$ electrons in an octahedral field [5]:

$${}^{4}A_{2} \rightarrow {}^{4}T_{2} = \Delta$$
 ${}^{4}A_{2} \rightarrow {}^{4}T_{1} = 7.5B + 1.5\Delta - (b^{-})$

In the equations, $b^- = \frac{1}{2} [(9B - \Delta)^2 + 144B^2]^{1/2}$,于是有

then we have
$$\frac{E_2(^4T_1)}{E_1(^4T_2)} = \frac{1}{A/B} \left\{ 7.5 + 1.5 \Delta/B - \frac{1}{2} \sqrt{(9 - (\Delta/B)^2 + 144)} \right\} = f(\Delta/B)$$
 let
$$E_2 = 20032 \, \mathrm{cm}^{-1}, \ E_1 = 14124 \, \mathrm{cm}^{-1},$$

Plot a graph $f(\Delta/B)\sim\Delta/B$, and then we obtain $\Delta/B=23.5$, $B=601\text{cm}^{-1}$, and $C\approx4B=2404\text{cm}^{-1}$. Since $\text{ZnWO}_4:\text{Cr}^{3\dagger}$ are monoclinic crystals, octahedral $\text{Cr}^{3\dagger}-\text{O}$ is seriously deformed, causing a further split of the $^4\text{T}_1$ and $^4\text{T}_2$ energy levels of $\text{Cr}^{3\dagger}$ ions. The $^4\text{T}_1$ level splits into 205706cm^{-1} (487nm) and 19531cm^{-1} (513nm). The $^4\text{T}_2$ level splits into three levels $\mathcal{E}=14706\text{cm}^{-1}$, $\mathcal{G}=14205\text{cm}^{-1}$, and $\eta=13549\text{cm}^{-1}$. In the polarized absorption spectrogram of E//C in Fig. 1b, there is a 2E peak in the vicinity of 810nm. From Fig. 1, we can see that the polarization property is very clear. For instance, when the direction of light passage is [100], there

is a considerable difference in light spectra of E//C and E//b. When the direction of light passage is [010], there is also little difference between shapes of light spectra for E//C and E//a, and the absorption value is much higher than that of E//a; these facts should be considered in experiments on laser excitation.




Fig. 2 Excitation spectra of ZnWO₄:Cr³⁺ crystal at room temperature (λ_{em}=920 nm)

—Cr₂O₃ 0.01% wt concentration

---- Or2O3 0.1% wt concentration

Fig. 1 Absorption spectra of
ZnWO4:Cr³⁺ crystal
(a) optical direction (100)⁴;
(b) optical direction (100)

1.2. Excitation light spectra


Fig. 2 shows the light excitation spectra of ZnWO4:Cr³+. The excitation spectra are measured with the Daojin [Japanese name in Chinese pronunciation] RF-540 fluorescence spectrograph. If 912nm is used as the monitoring wavelength, the resulting excitation spectra is related to the Cr³+ dopant concentration. When the Cr³+ dopant concentration is greater than 0.05%, the excitation peak is at 608nm. When the concentration is less than 0.05%, the peak moves to 622.4nm. This shift is related to adjustment of the crystal lattice. As shown by x-ray analysis,

when the ${\rm Cr}^{3+}$ dopant concentration is 0.05%, the crystal cell volume is at a minimum. Therefore, when the lattice position occupied by ${\rm Cr}^{3+}$ is such that the dopant concentration is high, the Cr-O spacing changes, causing two different positions for the excitation absorption peaks. In the authors' view, this excitation absorption peak is caused by the ${}^2{\rm T}_1$ energy level split off from the ${}^2{\rm G}$ energy level.

1.3. Fluorescence spectra

Fluorescence spectra are measured with the RF-540 fluorescence spectrograph. To monitor with the instrument, a photoelectric multiplier is used, the multiplier is of the same type as that used in light measurements, such that the influence of a change in light source intensity can be eliminated. Fig. 3 is the fluorescence spectra based on the energy level position of the absorption spectra while fixing the excitation wavelength. Relative to the fluorescence peak intensity, the change is minor. It can be determined that these three energy levels are $^4\mathrm{T}_2$ as the result of low-symmetry splitting. From Fig. 4, we can see that Stokes displacement is very close after splitting of the $^4\mathrm{T}_2$ energy level, at 3753, 3567, and 3345cm $^{-1}$, respectively. These are caused by oscillation of the crystal lattice. With the red shift in wavelength, Stokes displacement also slightly increases in value.

The dopant concentration also considerably influences Cr³⁺ luminescence. Fig. 6 indicates the influence on fluorescence intensity due to the dopant concentration. When the concentration is between 0.005 and 0.01% by weight, the fluorescence is the most intense. With increase in concentration later on, the fluorescence drops exponentially. At 0.05% by weight, the luminescence intensity again begins to increase. However, after the concentration becomes greater than 0.08% by






Fig. 3 Emission spectra of ZnWO₄:Cr³⁺ crytsal at room temperature

Fig. 4 Energy level diagram of Cr³⁺ in ZnWO₄: Cr³⁺ crystal

weight, the luminescence intensity begins to saturate. However, in the vicinity of 0.1% weight, concentration quenching sets in, thus the luminescence intensity clearly decreases.

Fig. 6 shows the different kind of influence on luminescence with variation in excitation wavelength. The fluorescence peak is the strongest when excited with 608nm. This is possibly caused by energy shift in 2T_1 and 4T_2 energy levels. However, it is not easily available for intensive excitation source at 608nm, so excitation is at the 532nm wavelength (double frequency Nd $^{3+}$:YAG laser). Although the intensity drops quite drastically, the position of the wavelength peak is the same, and the bandwidths are close to each other. However, there is still sufficient intensity, therefore ${\rm ZnWO}_4$:Cr $^{3+}$ is a very promising new kind of laser crystal.




Fig. 5 Effect of Cr³⁺ ion concentration on emission intensity




Fig. 6 Emission spectra excited by various wavelengths

Wang Liangmao took part in growing the crystals. Comrade Xu Zuyan, of the Institute of Physics of the Chinese Academy of Sciences, gave much assistance in the experiments on laser excitation. The authors express their gratitude to both of them. In addition, the authors are grateful to professor Zhang Kecong, for his concern and guidance in the investigation.

The research was funded by the State Natural Science Foundation. The paper was received for publication on 21 November 1989.

REFERENCES

- 1 G. Huber et al., J. Luminescence, 39, 259~268 (1988)
- 2 D. Vivien et al. J. Luminescence, 39, 29~33 (1987)
- 3 K. Petermann et al., J. Luminescence, 31 & 32, 71~77 (1984)
- 4 W. Kolbe et al., IEEE J. Quant. Electr., QE-21 (10), 1596 (1985)
- 5. Marfunin, A.S., <u>Kuangwu wulixue daolun</u> [Mineral Physics], Geology Publishing House, 1984, p. 67.

DISTRIBUTION LIST

DISTRIBUTION DIRECT TO RECIPIENT

ORGANIZATION	MICROFICHE
BO85 DIA/RIS-2FI	1
C509 BALLOC509 BALLISTIC RES LAB	1
C510 R&T LABS/AVEADCOM	1
C513 ARRADCOM	1
C535 AVRADCOM/TSARCOM	1
C539 TRASANA	1
Q592 FSTC	4
Q619 MSIC REDSTONE	1
Q008 NTIC	1
Q043 AFMIC-IS	1
E051 HQ USAF/INET	1
E404 AEDC/DOF	1
E408 AFWL	1
E410 AFDIC/IN	1
E429 SD/IND	1
POO5 DOE/ISA/DDI	1
P050 CTA/OCR/ADD/SD	2
1051 AFIT/LDE	1
PO90 NSA/CDB	1
2206 FSL	1

Microfiche Nbr: FTD95C000131

NAIC-ID(RS)T-0496-94